



# Xitanium LED downlight and spotlight drivers

## XITANIUM 50W WH 0.7-1.5A 54V SR IS 230V

Xitanium LED drivers are leading the way in terms of reliability

### Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	1500 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	50 W
Output Power (Min)	16.8 W
Output Current (Min)	700 mA
Output Voltage (Max)	54 V
Output Voltage (Min)	24 V
Protection class IEC	Safety class I/II
System characteristics	
Central DC Operation	Yes
YellowDot ready	No
Temperature	
T-Case Lifetime (Max)	80 °C

T-Case Maximum (Max)	90 °C
Controls and Dimming	
Dimmable	DALI
Mechanical and Housing	
Product Length	200 mm
Overall length	201 mm
Overall width	75 mm
Overall height	32.5 mm
Dimensions (Height x Width x Depth)	33 x 75 x 201 mm
Ingress protection code	IP20 [Finger-protected]
Net Weight (Piece)	0.225 kg
Approval and Application	
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	DALI, NFC

## Xtanium LED downlight and spotlight drivers

### Product Data

Order product name	XITANIUM 50W WH 0.7-1.5A 54V SR IS 230V
Full product name	XITANIUM 50W WH 0.7-1.5A 54V SR IS 230V
Full product code	871951432694100
Order code	929002861306
Material Nr. (12NC)	929002861306

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514326941
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514326958

